

Premium Plus+™ Tubing



Features

- Bowsmith Premium Plus+ tubing is manufactured from the highest grades of polyethylene resins.
- Contains a minimum of 2% carbon black.
- Every reel undergoes a series of tests to insure Bowsmith's high quality manufacturing standards are met.
- Available in a wide range of diameters, wall thickness and coil lengths to accommodate required lengths of run, working pressures and terrain.
- Pre-punched and marked custom spacing are available for easy Fan-Jet® microsprinkler or NonStop® emitter installations.
- Manufactured in Exeter, California and Avon Park, Florida.
- Seven-year warranty backs it all up. (See warranty for details)

Dimensions

Size Designation*	Nominal Tubing Size			Pressure Rating	Coil Length (in.)	
	Outside Diam (in.)	Wall Thickness (in.)	Inside Diam (in.)		Standard	Custom
490P40	0.490	0.040	0.410	70	2000'	
590P40	0.590	0.040	0.510	58	1000'	
625P48	0.625	0.048	0.530	67	1000'	100', 500'
625P50	0.625	0.050	0.525	71	1000'	100', 500'
620/710	0.715	0.0475	0.620	57	1000'	100', 500'
700P48	0.700	0.048	0.605	59	1000'	100', 500'
700P50	0.700	0.050	0.600	63	1000'	100', 500'
700P55	0.700	0.055	0.590	70	1000'	100', 500'
720P48	0.720	0.048	0.625	57	1000'	500'
795P52	0.795	0.053	0.690	57	1000'	500'
720/820	0.825	0.0525	0.720	55	1000'	500'
835P52	0.835	0.053	0.730	55	1000'	500'
935P62	0.935	0.063	0.811	57	1000'	500'
935P58	0.935	0.058	0.822	55	1000'	500'
3/4"-50	0.916	0.055	0.805	54	1000'	500'
1195P72	1.195	0.073	1.050	53	500', 660'	
1"-45	1.190	0.064	1.060	49	500', 660'	
1530P72	1.530	0.075	1.380	42	400'	
1-1/4"-50	1.540	0.0865	1.365	50	300'	